

Data Types and Basic Calculation

Intrinsic Data Types

Fortran supports **five** intrinsic data types:

1. **INTEGER** for exact **whole numbers**

e.g., 1, 100, 534, -18, -654321, etc.

2. **REAL** for approximate, **fractional numbers**

e.g., 1.1, 3.0, 23.565, 3.1415, exp(1), etc.

3. **COMPLEX** for complex, **fractional numbers**

e.g., (1.1, -23.565), etc.

4. **LOGICAL** for **truth values** (boolean)

These may only have values of true or false
e.g., **.TRUE.**, **.FALSE.**

5. **CHARACTER** for **strings** of characters

e.g., **'?'**, **'Albert Einstein'**, **'X + Y = '**, etc.

The string length is part of the **type** in Fortran.

Integers (1)

Fortran uses **integers** for:

- **Loop counts** and **loop limits**
- An **index** into an **array** or a position in a list
- An **index** of a **character** in a **string**
- As **error codes**, **type categories**, etc.

Also use them for purely **integral values**

Example: Calculations involving **counts**

Integers (2)

- Integers are restricted to lie in a finite range.

Typically ± 2147483647 (Sometimes $\pm 9.23 \times 10^{17}$)

- A compiler may allow you to select the range.
- More on arithmetic and errors later.

Reals

- Reals are used for continuously varying values.
- Reals are stored as floating-point values. They also have a finite range and precision.

THEY ARE INEXACT

- It is essential to use floating-point appropriately.

FP representation : significand x base^{exponent}

$$1.2345 = 12345 \times 10^{-4}$$

Floating Point Standard

- The **Institute of Electrical and Electronics Engineers (IEEE)** has produced a standard for floating point arithmetic. **IEEE 754-2008**.
- This defines 32-bit and 64-bit floating point representations.
- **32-bit**: 10^{-38} to 10^{+38} and **6-7** decimal places
- **64-bit**: 10^{-308} to 10^{+308} and **15-16** decimal places

Real Constants

- Real constants **must** contain a **decimal point** or an **exponent**.
- They can have an optional **sign** just like **integers**.
- The basic fixed-point form is anything like:
123.456, -123.0, +0.0123, 123., .0123,
0012.3, 0.0, 000., .000
- Optionally followed by **E** or **e** and an exponent
1.0e6, 123.0e-3, .0123e+5, 123.E+06, .0E0
- **1e6** and **1E6** are also valid Fortran **real constants**.

Complex Numbers

This course will generally ignore them.
If you don't know what they are don't worry.

These are (**real**, **imaginary**) pairs of **REALs** (i.e., **Cartesian** notation)

Constants are pairs of reals in parentheses
e.g., **(1.23,-4.56)** or **(-1.0e-3,0.987)**

Declaring Numeric Variables

Variables hold values of different types:

INTEGER :: count, income, mark

REAL :: width, depth, height

You can get all **undeclared variables** diagnosed
Add the statement **IMPLICIT NONE** at the
start of every **program, subroutine, function**, etc.

If not, variables are **declared implicitly** by use

Names starting with **I-N** are **INTEGER**

Names starting with **A-H** and **O-Z** are **REAL**

YOU SHOULD ALWAYS
USE IMPLICIT NONE

Assignment Statements

The general form is:

`<variable> = <expression>`

This is actually very powerful (see later).

This **first** evaluates the **expression** on the **RHS**.

It **then** stores the result in the **variable** on the **LHS**.

It replaces whatever value was there before.

For example:

`xyMax = 2 * xyMin`

`mySum = mySum + Term1 + Term2 + (Eps * Err)`

Arithmetic Operators

There are **five** built-in numeric operations:

- + addition
- subtraction
- * multiplication
- / division
- ** exponentiation

Exponents can be any arithmetic type:

INTEGER, REAL or COMPLEX

Examples

Some examples of arithmetic expressions are:

$$A + B * C$$

$$A + C1 - D2$$

$$X + Y/7.0$$

$$2**K$$

$$A**B + C$$

$$(A + C1) - D2$$

$$A + (C1 - D2)$$

$$P**3/((X+Y*Z)/7.0-52.0)$$

Operator Precedence

Fortran uses normal mathematical conventions

- Operators bind according to **precedence**
- And then generally from **left** to **right**
- Exponentiation binds from **right** to **left**

The **precedence** from **highest** to **lowest** is:

- **** **exponentiation**
- * /** **multiplication and division**
- + -** **addition and subtraction**

Parentheses are used to control it. Use them whenever the **order matters** or it is **clearer**.

Examples

$X + Y * Z$ is equivalent to $X + (Y * Z)$
 $X + Y / 7.0$ is equivalent to $X + (Y / 7.0)$
 $A - B + C$ is equivalent to $(A - B) + C$
 $A + B ** C$ is equivalent to $A + (B ** C)$
 $-A ** 2$ is equivalent to $-(A ** 2)$
 $A - (((B + C)))$ is equivalent to $A - (B + C)$

You can force any order you like:

$$(X + Y) * Z$$

Adds X to Y and **then** multiplies by Z

Exponentiation Precedence

This is an exception as it evaluates **right to left**.

$2 ** 3 ** 2$ is equivalent to $2 ** (3 ** 2)$
 $\implies 2 ** 9 = 512$

NOT $8 ** 2 = 64$

In case you actually try to do this (???)

Integer Expressions

Expressions involving integer constants and variables

These are evaluated in integer arithmetic. Division always truncates toward zero.

INTEGER :: K, L, N

$N = K + L / 2$

If $K = 4$ and $L = 5$ then $N = 6$

$(-7)/3$ and $7/(-3)$ are both -2

Mixed Expressions

In the CPU calculations must be performed between objects of the same **type**, so if an expression mixes type some objects must change type.

Default types have an implied ordering:

1. INTEGER (**lowest**)
2. REAL
3. COMPLEX (**highest**)

The result of an expression is always of the **highest** type. e.g., **INTEGER * REAL** gives a **REAL**

Be careful with this as it can be deceptive!

Conversions

There are several ways to force conversion

- **Intrinsic functions** `INT`, `REAL` and `COMPLEX`

$$X = X + \text{REAL}(K)/2$$

$$N = 100 * \text{INT}(X/1.25) + 25$$

- Use the appropriate constants. (You can even add zero or multiply by one)

$$X = X + K/2.0$$

$$X = X + (K + 0.0)/2$$

The second method isn't very nice but works well enough. (See later about `KIND` and precision)

Mixed-type Assignment

<real variable> = <integer expression>

- The RHS is converted to REAL
- Just as in a mixed-type expression

<integer variable> = <real expression>

- The RHS is truncated to INTEGER
- It is always truncated toward zero

Similar remarks apply to COMPLEX

The RHS is evaluated independently of the LHS

Example: **mixedassigned.f90**

Intrinsic Functions

Built-in functions that are always available

- No **declaration** is needed -- just use them!

Examples:

```
Y = SQRT(X)
```

```
PI = 4.0 * ATAN(1.0)
```

```
Z = EXP(3.0*Y)
```

```
X = REAL(N)
```

```
N = INT(X)
```

```
Y = SQRT(-2.0*LOG(X))
```

Intrinsic Numeric Functions

- REAL(n) ! Converts its argument to REAL
- INT(x) ! Truncates x to INTEGER (to zero)
- AINT(x) ! The result remains REAL
- NINT(x) ! Converts x to the nearest INTEGER
- ANINT(x) ! The result remains REAL
- ABS(x) ! The absolute value of its argument
 - ! Can be used for INTEGER, REAL or COMPLEX
- MAX(x,y,...) ! The maximum of its arguments
- MIN(x,y,...) ! The minimum of its arguments
- MOD(x,y) ! Returns x modulo y

And there are more -- some are mentioned later.

Intrinsic Mathematical Functions

$\text{SQRT}(x)$! The square root of x
$\text{EXP}(x)$! e raised to the power of x
$\text{LOG}(x)$! The natural logarithm of x
$\text{LOG10}(x)$! The base 10 logarithm of x
$\text{SIN}(x)$! The sine of x (x in radians)
$\text{COS}(x)$! The cosine of x (x in radians)
$\text{TAN}(x)$! The tangent of x (x in radians)
$\text{ASIN}(x)$! The arc sine of x (x in radians)
$\text{ACOS}(x)$! The arc cosine of x (x in radians)
$\text{ATAN}(x)$! The arc tangent of x (x in radians)

Logical Type

These can take only two values: **true** or **false**

`.TRUE.` and `.FALSE.`

- Their type is `LOGICAL` (not `BOOL`)

`LOGICAL :: red, amber, green`

`red = .True.`

`IF (red) THEN`

`PRINT *, 'Stop'`

`red = .False.; amber = .True.; green = .False.`

`ELSE IF (red .AND. amber) THEN`

...

Relational Operators

Relations create **LOGICAL** values

These can be used on **any other** built-in type

== (or **.EQ.**) equal to

/= (or **.NE.**) not equal to

These can be used only on **INTEGER** and **REAL**

< (or **.LT.**) less than

<= (or **.LE.**) less than or equal to

> (or **.GT.**) greater than

>= (or **.GE.**) greater than or equal to

Logical Expressions

Can be as complicated as you like

Start with `.TRUE.`, `.FALSE.` and `relations`

Can use `parentheses` as for numeric ones

`.NOT.`, `.AND.` and `.OR.`

`.EQV.` can be used instead of `==`

`.NEQV.` can be used instead of `/=`

Fortran is not like C-derived languages

`LOGICAL` is not a sort of `INTEGER`

Example: `testlogical.f90`

Operator Precedence (2)

Include the logical and relational operators

The **precedence** from **highest** to **lowest** is:

.not. (-)	logical NOT and negative sign
**	exponentiation
* /	multiplication and division
+ -	addition and subtraction
<, <=, >, >=	relational
.and.	logical AND
.or.	logical OR
=	assignment

Character Type

Used when **strings of characters** are required.
Names, descriptions, headings, etc.

Fortran's basic type is a **fixed-length string** (unlike almost all more recent languages)

Character constants are **quoted strings**

```
PRINT *, 'This is a title'
```

```
PRINT *, "And so is this"
```

The **characters** between **quotes** are the **value**

Character Data

The **case of letters** is significant in them

Multiple spaces are not equivalent to one space

Any **representable character** may be used

The **only** Fortran syntax where the above is so

In 'Time^^=^^|3:|5', with '^' being a space

The character string is of length **14**

Character **1** is T, **8** is a space, **10** is |, etc.

Example program: **charstrings.f90**

Character Variables

CHARACTER :: answer, marital_status

CHARACTER(LEN=10) :: name, dept, faculty

CHARACTER(LEN=32) :: address

answer and marital_status are each of length 1

They hold precisely one character each

answer might be blank or hold 'Y' or 'N'

name, dept and faculty are of length 10

address is of length 32

Another Form

```
CHARACTER :: answer*1, martial_status*1, &  
name*10, dept*10, faculty*10, address*32
```

While this form is historical it is more compact

Don't mix the forms -- that is an abomination

```
CHARACTER(LEN=10) :: dept, faculty, addr*32
```

For some obscure reasons using `LEN=` is cleaner
It avoids some arcane syntactic “gotchas”

Character Assignment

```
CHARACTER(LEN=6) :: firstname, lastname  
firstname = 'Mark' ; lastname = 'Branson'
```

firstname is padded with spaces ('Mark^^')
lastname is truncated to fit ('Branso')

Unfortunately you won't get told
But at least it won't overwrite something else

Character Concatenation

Values may be **joined** using the `//` operator

```
CHARACTER(LEN=6) :: identity, A, B, Z
```

```
identity = 'TH' // 'OMAS'
```

```
A = 'TH'; B = 'OMAS'
```

```
Z = A // B
```

Sets `identity` to 'THOMAS'

But `Z` is set to 'TH' – **why?**

`//` does not remove **trailing spaces**

It used the whole length of its inputs

Substrings

If Name has length 9 and holds 'Marmaduke'

Name(1:1) would refer to 'M'

Name(2:4) would refer to 'arm'

Name(6:.) would refer to 'duke' -- note the form!

We could therefore write statements such as

```
CHARACTER :: name*15, lastname*7, title*3
```

```
name = 'Mr. Joe Johnson'
```

```
title = name(1:3)
```

```
lastname = name(9:)
```

Warning - a “Gotcha”

CHARACTER substrings look like array sections
But there is no equivalent of array indexing

```
CHARACTER :: name*20, temp*1  
temp = name(10)
```

name(10) is an implicit function call

Use name(10:10) to get the 10th character

CHARACTER variables come in various lengths
name is **not** made up of 20 variables of length 1

Intrinsic Character Functions

LEN(c) ! The STORAGE length of c
TRIM(c) ! c without trailing blanks
ADJUSTL(c) ! With leading blanks removed
INDEX(str,sub) ! Position of sub in str
SCAN(str,set) ! Position of any character in set
REPEAT(str,num) ! num copies of str, joined

And there are more -- see the references

Examples

```
name = '  Smith  '  
newname = TRIM(ADJUSTL(name))
```

newname would contain 'Smith'

```
CHARACTER(LEN=6) :: A, B, Z  
A = 'TH'; B = 'OMAS'  
Z = TRIM(A) // B
```

Now Z gets set to 'THOMAS' correctly

Named Constants (1)

These have the `PARAMETER` attribute

```
REAL, PARAMETER :: pi = 3.14159
```

```
INTEGER, PARAMETER :: maxlen = 100
```

They can be used anywhere a `constant` can be

```
CHARACTER(LEN=maxlen) :: string
```

```
circum = pi * diam
```

```
IF (nchars < maxlen) THEN
```

```
...
```

Named Constants (2)

Why are these important?

They reduce mistyping errors in long numbers

Is `3.14159265358979323846D0` correct?

They can make equations much clearer

Much clearer which constant is being used

They make it easier to modify the program later

`INTEGER, PARAMETER :: MAX_DIMENSION = 10000`

Named Character Constants

```
CHARACTER(LEN=*), PARAMETER :: &  
    author = 'Dickens', title = 'A Tale of Two Cities'
```

LEN=* takes the length from the data

It is permitted to define the **length** of a constant
The data will be **padded** or **truncated** if needed

But the above form is generally the best

Named Constants (3)

Expressions are allowed in constant values

```
REAL, PARAMETER :: pi = 3.1415, &  
    pi_by_4 = pi/4, two_pi = 2*pi
```

```
CHARACTER(LEN=*), PARAMETER :: &  
    all_names = 'Bob, Jennifer, Karen', &  
    karen = all_names(16:20)
```

Generally anything reasonable is allowed
It must be determinable at compile time

Initialization

Variables start with **undefined** values
They often vary from run to run, too

Initialization is much like defining constants
without the **PARAMETER** attribute

```
INTEGER :: count = 0, I = 5, J = 100
```

```
REAL :: inc = 1.0E5, max = 10.0E5, min = -10.0E5
```

```
CHARACTER(LEN=10) :: light = 'Amber'
```

```
LOGICAL :: red = .TRUE., blue = .FALSE, &  
          green = .FALSE.
```